

DS-2CE16D0T-IT1E 2 MP PoC Fixed Bullet Camera



- 2 MP PoC bullet camera
- EXIR 2.0: advanced infrared technology with 20 m IR distance
- Water and dust resistant (IP67)
- Transmits both HD video and power over the same coaxial cable

▪ Specification

Camera	
Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.01 Lux @ (F2.0, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
Day & Night	IR Cut Filter
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 180°, Rotation: 0 to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm, 3.6 mm and 6 mm fixed focal lens
Focal Length & FOV	Horizontal FOV: 103.55° (2.8 mm), 82.63° (3.6 mm), 54.38° (6 mm)
Lens Mount	M12
Illuminator	
Supplement Light Type	IR
Supplement Light Range	Up to 20 m
Smart Supplement Light	Yes
Image	
Image Settings	Brightness, Mirror, Sharpness, AGC
Frame Rate	PAL: 1080p @ 25 fps NTSC: 1080p @ 30 fps
Day/Night Mode	Auto/Color/BW (Black and White)
Wide Dynamic Range (WDR)	Digital WDR
Image Enhancement	BLC, HLC, Global
Noise Reduction	2D DNR
Interface	
Video Output	1 HD analog output
General	
Power	12 VDC ± 30%/PoC.af, max. 3 W
Material	Front cover: Metal, Main body: Plastic
Dimension	86.7 mm × 81.6 mm × 226 mm (3.4" × 3.2" × 8.9")
Weight	Approx. 430 g (0.95 lb)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity 90% or less (non-condensing)
Communication	HIKVISION-C
Language	English
Approval	
Protection	IP67

▪ Available Model

DS-2CE16D0T-IT1E(2.8mm)

DS-2CE16D0T-IT1E(3.6mm)

DS-2CE16D0T-IT1E(6mm)

▪ **Accessory**

▪ **Optional**

**DS-1280ZJ-XS
Junction Box**



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

