

[Get a Quote](#)

## Overview

---

16-ch 5 MP 1U H.265 DVR

## Quick Specs

---

Figure 1 shows the appearance of DS-7216HUHI-K2.



Table 1 shows the Quick Specs.

Product Code	DS-7216HUHI-K2
IP Video Input	16-ch (up to 32-ch) Up to 8 MP resolution Support H.265+/H.265/H.264+/H.264 IP cameras
Video Bit Rate	32 Kbps to 10 Mbps
Audio Bit Rate	64 Kbps
Power Supply	12 VDC
Consumption (Without HDD)	≤ 25 W
Dimension (W × D × H)	380 × 320 × 48 mm (15.0 × 12.6 × 1.9 inch)

## Product Details

Figure 2 shows the front panel of DS-7216HUHI-K2.



DS-7216HUHI-K2 provides these features and benefits:

- 16 channels and 2 HDDs 1U DVR
- Efficient H.265 pro+ compression technology
- Encoding ability up to 8 MP @ 8 fps, 5 MP @ 12 fps
- 5 signals input adaptively (HDTVI/AHD/CVI/CVBS/IP)
- Up to 32 network cameras can be connected

## Get More Information

Do you have any question about the **DS-7216HUHI-K2** ?

Contact us now via [Live Chat](#) or [sales@router-switch.com](mailto:sales@router-switch.com).

## Specification

DS-7216HUHI-K2 Specification	
<b>Model</b>	DS-7216HUHI-K2
<b>Recording</b>	
<b>Video Compression</b>	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
<b>Encoding Resolution</b>	8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF
<b>Frame Rate</b>	Main stream: ,8 MP@8fps/5 MP@12fps/4 MP@15fps/3 MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N),Sub-stream: ,WD1/4CIF/CIF@25fps (P)/30fps (N)
<b>Video Bit Rate</b>	32 Kbps to 10 Mbps
<b>Dual Stream</b>	Support
<b>Stream Type</b>	Video, Video & Audio
<b>Audio Compression</b>	G.711u
<b>Audio Bit Rate</b>	64 Kbps
<b>Video And Audio</b>	
<b>IP Video Input</b>	16-ch (up to 32-ch) Up to 8 MP resolution Support H.265+/H.265/H.264+/H.264 IP cameras
<b>Analog Video Input</b>	16-ch BNC interface (1.0 Vp-p, 75Ω), supporting coaxitron connection
<b>AHD Input</b>	5 MP, 4 MP, 1080p25, 1080p30, 720p25, 720p30
<b>HDCVI Input</b>	4 MP, 1080p25, 1080p30, 720p25, 720p30
<b>CVBS Input</b>	PAL/NTSC
<b>Audio Input</b>	4-ch, RCA (2.0 Vp-p, 1 KΩ)
<b>Audio Output</b>	1-ch, RCA (Linear, 1 KΩ)
<b>Two-Way Audio</b>	1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the first audio input)
<b>Synchronous Playback</b>	16-ch
<b>HDTVI Input</b>	8 MP, 5 MP, 4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25
<b>VGA/HDMI Output</b>	VGA: 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz,HDMI: 1-ch, 4K (3840 × 2160)/30Hz, ,2K (2560 × 1440)/60Hz,,1920 × 1080/60Hz, 1280 × 1024/60Hz, ,1280 × 720/60Hz, 1024 × 768/60Hz

CVBS Output	1-ch, BNC (1.0 Vp-p, 75Ω)
<b>Network</b>	
Remote Connections	128
Network Protocols	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF
Network Interface	1, RJ45 10M/100M/1000M self-adaptive Ethernet interface
<b>Auxiliary Interface</b>	
SATA	2 SATA interfaces
Capacity	Up to 10 TB capacity for each disk
Alarm In/Out	16/4
USB Interface	Front panel: 1 × USB 2.0,Rear panel: 1 × USB 3.0
Serial Interface	RS-485 (half-duplex)
<b>General</b>	
Power Supply	12 VDC
Working Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Working Humidity	10 to 90 %
Dimension (W × D × H)	380 × 320 × 48 mm (15.0 × 12.6 × 1.9 inch)
Consumption (Without HDD)	≤ 25 W

## Want to Buy

[Order Now](#)
[Get a Quote](#)

## Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

## Contact Us

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: [sales@router-switch.com](mailto:sales@router-switch.com)